

VARISOFT® 222 LM (90 %)

Product description

VARISOFT® 222 LM (90 %) is a ditallow diamidoamine ethoxylated quaternary softener concentrate. VARISOFT® 222 LM (90%) is a fluid, cold-water dispersible softener concentrate.

Physical properties

Appearance 20 °C	Light yellow liquid
Gardner Colour	Max. 6
Solids %	84 – 87
pH (5 % in IPA/water)	5.0 – 6.5
IPA %	7.5 – 9.5
Flash point, PMCC	29 °C

Application

- VARISOFT® 222 LM (90 %) is recommended for finishing and preparation of yarns, woven and knit goods made of natural and synthetic fibers (polyester, polyamide, polyacrylonitrile), as well as their blends.
- VARISOFT® 222 LM (90 %) is particularly recommended for the treatment of cotton and cotton blends such as knit, twill and terry cloth.
- VARISOFT® 222 LM (90 %) is suitable for application as a single component from aqueous dilutions by padding or the exhaust method.
- For economical performance enhancement, VARISOFT® 222 LM (90 %) is easily formulated with alkylpolyether siloxanes or α , ∞ silicone diquaternary softeners.

Benefits

- VARISOFT® 222 LM (90 %) is economical to use.
- VARISOFT® 222 LM (90 %) is highly substantive and imparts a soft, dry, fluffy hand to treated goods.
- White goods treated with VARISOFT® 222 LM (90 %) show very little yellowing.
- VARISOFT® 222 LM (90 %) is a flowable concentrate which is readily dispersible in water in concentration ranges of 3 – 25 % actives.
- On nylon, polyester, acrylic and polypropylene fabrics, VARISOFT® 222 LM (90 %) exhibits excellent antistatic properties.
- Independent testing of VARISOFT® 222 LM (90%) confirms antiozonate properties.
- VARISOFT® 222 LM (90 %) is resistant to phenolic yellowing.
- VARISOFT® 222 LM (90 %) is a cationic surfactant compatible with nonionic, amphoteric and cationic finishing products.
- VARISOFT® 222 LM (90 %) exhibits good stability to acids, alkalis, electrolytes and hardness salts.

Registration status

VARISOFT® 222 LM (90 %) is listed on the TSCA inventory.

VARISOFT® 222 LM (90 %) is cleared for the following international inventories:

Korea (ECL), China, Canada (DSL), Australia (AICS), Philippines (PICCS)

Storage stability

VARISOFT® 222 LM (90 %) can be stored in the original sealed containers at room temperature for 12 months. To ensure homogeneity after prolonged storage or transport, it is recommended that the material is stirred prior to use. For additional storage and handling information, please refer to the material safety data sheet.

Packaging

VARISOFT® 222 LM (90%) is packaged in specially lined, open-head steel drums, 193 kg net weight. It is also available in bulk quantities.

Hazardous goods classification

Information concerning

- classification and labeling according to regulations for transport of chemicals
- protective measures for storage and handling
- measures in case of accidents and fires
- toxicity and ecological effects

is given in our material safety data sheets.

06/2015

Trademark notice and legal notice

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

(Status: June 2015)

Evonik Nutrition & Care GmbH

Goldschmidtstr. 100, 45127 Essen, Germany

Phone Europe +49 201 173-2665, Asia +86 21 61191 125, Americas +1 804 727 0700

interface-performance@evonik.com, www.evonik.com/interface-performance

Evonik. Power to create.



Evonik. Power to create.

